


The logo for SERRA*MAT, featuring the brand name in a bold, sans-serif font. The asterisk is stylized with a multi-colored starburst effect in shades of red, orange, yellow, and green.

Quality Matting Solutions

Mats

Obex® Tergo

Modular tile matting systems
with textile scapers inserts

A photograph showing a modern building entrance with a curved glass door. The floor is covered with a large, textured grey carpet matting system, which is installed outdoors in a sheltered area. The matting system consists of rectangular tiles with a woven, grid-like pattern. The entrance is brightly lit, and the matting system is shown in a clean, well-maintained state.

**Terga tiles can be installed outdoors,
underneath a sheltered area**

PROUD DISTRIBUTOR OF *Miliken*



Tergo tiles as first line of defence, can be combined with Forma™ tiles for a complete entrance matting solution.

Tergo 16C combined with Atrium Plus™

Technical Specifications: Tergo

Product Information	Tergo 11C	Tergo 16	Tergo 16C
Textile construction	100% mono filaments of polyamide 6.6 in tufted cut pile		
Tile material	UV resistant PVC		
Tile construction	Closed	Open	Closed
Total thickness in mm	11	16	16
Total weight in kg per m ²	6.82	9.08	10.37
Outdoor temperature resistance	From - 30°C up to + 50°C		
Ozone resistance	50 pphm ozone 30°C		
Wear resistance - Vetterman test	22,000 cycles		
Fire resistance test	BS 4790		
Tile size in mm	Nominal 200x200 - Useable 195x195 when installed		
Tile colour	Graphite		

All specifications are according to ISO 9001 Quality certification and ISO 14001 Environmental certification, and are subject to change to meet the ongoing improvements and innovation of our products.

Serra®MAT™ – A division of SERRA SERVICES (Pty) Ltd

Email : info@serra.co.za

Tel : +27 (0)11 334-7447

Fax : +27 (0)11 334-7165 or +27 (0)11 334-9858

Web : www.serra.co.za & www.serramat.co.za

Postal: PO Box 1217 Southdale, South Africa, 2135



www.serramat.co.za